



Armação positiva das lajes do PAVIMENTO TERREO

escala 1:50

RELAÇÃO DO AÇO				
Positivos				
AÇO	N	DIAM (mm)	QUANT	C.TOTAL (cm)
CA60	1	5.0	62	374
	2	5.0	12	565
	3	5.0	50	374
	4	5.0	14	194
CA50	5	5.0	8	558
	6	5.0	8	299
	7	5.0	14	224
	8	6.3	14	484
	9	6.3	14	284
	10	6.3	15	305
	11	6.3	3	334
	12	6.3	3	298
	13	6.3	3	499
	14	6.3	3	686
	15	6.3	3	299
	16	6.3	10	335
	17	6.3	6	586
	18	6.3	6	194
	19	6.3	6	190
	20	6.3	14	545
	21	6.3	12	374
	22	6.3	4	468
	23	6.3	4	486
	24	6.3	9	752
	25	6.3	14	481
	26	6.3	12	374
	27	6.3	14	537
	28	6.3	6	194
	29	8.0	6	353
	30	10.0	7	412
	31	10.0	7	385
	32	10.0	7	410
	33	10.0	7	429

RESUMO DO AÇO			
AÇO	DIAM (mm)	C.TOTAL (m)	PESO ± 10% (kg)
CA50	6.3	734.5	197.7
	8.0	21.2	9.2
	10.0	114.5	77.7
CA60	5.0	613.8	104.1
PESO TOTAL (kg)			
CA50	284.6		
CA60	104.1		
Volume de concreto (C-30) = 31.36 m³			
Área de forma = 0.00 m²			